



Číslo pol.	Délka [m]	Počet ks.	Délka
4	V10 1.590	92	10 425
5	V12 12.000	12	144.000
6	V12 3.500	24	84.000
7	V10 1.180	92	108.560
Celková délka			254.840
Specifická hmotnost			0.617
Hmotnost [kg]			157.236
Hmotnost celkem			359.700

Č. pol.	D [mm]	Delka [m]	Počet ks.	Delka		
				10 425		
1	V16	3,450	9	V10	V16	
2	V16	4,205	9		31,050	37,845
3	V10	1,272	102		129,744	
Celková delka					129,744	68,895
Specifická hmotnosť					0,617	1,578
Hmotnosť celken					80,052	108,716
Hmotnosť celken					188,768	

PROJECT SITE

~~WHOEVER~~

THE GAB™ FOR CONSTRUCTION

Page 26 of 27

tb ... krytie pozdĺžnej vstupu
tb ... longitudinal reinforcement covering
KOTY VYSTUZE - OSOVO-STREDNICA
Dimensions of reinforc. - axial

⑦ - VIAZAT KU 'KARI' V DOSKE
- tie to 'KARI' at ceiling

BETON / Concrete: B20

VYSTUZ / Reinforcement: 10 425 (V)

HS HSV s.r.o. KOŠICE
Technický úsek

Technický úsek

4

±0,000=224,530m.n.m

50/

$$y = 2x$$

VE3
M 1:50

REZ 1-1
M 1:20

REZ 2-2
M 1:20

PRE1 - 3x
M 1:50

REZ 3-3
M 1:20 ②

80
⑦ $\phi V10/1180 - 92 \text{ K}$
1100
⑦

REFLEX-PRO

[illegible]

--	--	--

M 1:50

Copyright © 2006 John Wiley & Sons, Ltd. *J. Forecast.* 25, 103–124 (2006)
DOI: 10.1002/for

45x400 **K**

99

100

100

Date :	Name :
--------	--------

History file:	Rev
---------------	-----