

DF9 @A-B5 FMCB @M

	tolerances	HP GOX Nm3/h (min)	% of Contract Price	tolerances	MP GOX Nm3/h (min)	% of Contract Price	tolerances	MP GAN Nm3/h (min)	% of Contract Price	tolerances	LP GAN Nm3/h (min)	% of Contract Price	tolerances	LAR Nm3/h (min)	% of Contract Price	tolerances	Electric Energy Consumption kWh/h	% of Contract Price	Cumulative %
		< 19.950	remedy		<11.400	remedy		<17.860	remedy		<47.500	remedy		<1.235	remedy		> 29.288	remedy	
Minimum Acceptable values Deviation	5%	19.950	1	5%	11.400	1	5%	17.860	1	5%	47.500	1	5%	1.235	0,5	6,5%	29.288	0,5	5,0
	4%	20.160	0,7	4%	11.520	0,7	4%	18.048	0,7	4%	48.000	0,7	4%	1.248	0,4	6,0%	29.150	0,4	2,2
	3,5%	20.265	0,5	3,5%	11.580	0,5	3,5%	18.142	0,5	3,5%	48.250	0,5	3,5%	1.255	0,2	5,5%	29.013	0,2	1,4
	2%	20.580	0	2%	11.760	0	2%	18.424	0	2%	49.000	0	2%	1.274	0	5%	28.875	0	0
	Contractual Data	21.000	0	Contractual Data	12.000	0	Contractual Data	18.800	0	Contractual Data	50.000	0	Contractual Data	1.300	0		27.500	0	0

Production figures refer to production defined at point 2.2.1) of PI-25-0073 rev. 0 Technical Specification

Measurement / performance test is defined in "TS1064 Performance test procedure"